

ALUMINUM

DYNAHAULER®

Custom engineered for a medium duty chassis

The DynaHauler®/MDC dump truck body is designed to fit a medium duty truck and comes with many ready-to-work features. These include a 3/16" A-572 full width floor and a 2" x 4" x 1/4" structural tubing top rail (steel body), sideboards, cab protector, and more.

Rely on our experience

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 50+ years of experience to build you the dump truck you want – we'll build it to your specification and application.



Optional polished aluminum is available as shown in this picture.

ISO 9001:2008 Certified.
Quality products,
quality workmanship.

J&J Truck Bodies & Trailers is a division
of Somerset Welding & Steel, Inc.

**J&J TRUCK BODIES
& TRAILERS®**
Built for the Long Haul™

Call us today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR MEDIUM DUTY CHASSIS

STEEL STANDARD SPECIFICATIONS*

Length: 9' - 12'.

Cab Protector: 10 ga., high-tensile, 1/2 length/full width, load bearing.

Side Panels: 10 ga., high-tensile, 26" high, with 2" x 4" x 1/4" structural tubing top rail and 8" side boards. Front and rear posts plus three side posts. Sloped, dirt shedding rubrail.

Floor: 3/16", A-572, full width.

Understructure: 4" structural channel cross members on 12" centers (5.4lb./ft.). 6" I-beam longitudinals (12.5 lb./ft.).

Tailgate: 34" high. Includes tailgate chains and top standard tailgate hardware

Hoist: Exclusive J&J model 50725 DA, 15-ton with safety prop.

Lighting: Truck-Lite®, sealed and shock proof system. Body-up light and pto light with premium inside controls.

Other Standard Features: Self-cleaning inside shedder plate • Ladder and steps • Tarp rods • Rear mud flaps and front steel mud guards • Back-up alarm • Body-up indicator lamp.

POPULAR OPTIONS

Sides: 30"- 42" height, 8 ga., high tensile, 3/16" thickness.

Cab Protector: 1/4, 3/4, and full.

Floors: 1/4".

Understructure: 4" I-beam crossmembers.

Tailgate: 40" - 48". Aluminum and air operated gates are available. Offset top hardware • Fast latch • 3-way gate fork style with ground control

Hoist: Model 60825 DA under body hoist, front mount telescopic, twin telescopic, trunnion front mount.

Other: Spreader apron • Full depth rear post with full depth rear skirt • Air operated and hot shift PTO • Body heat • Load covers • Tool box • Coal doors • Pintle hook • Central hydraulics • Special lighting.

ALUMINUM STANDARD SPECIFICATIONS*

Length: 9' - 12'.

Cab Protector: 3/16" 5454-H34 1/2 length/full width, load bearing.

Side Panels: 3/16" 5454-H34 26" high, with 4" x 4" 6061-T6 extruded top rail and 8" side boards. Front and rear posts. Sloped, dirt shedding rubrail.

Floor: 1/4", 5454-H34 full width.

Understructure: 4" extruded I-beam cross members on 12" centers, 6061-T6. 6" extruded I-beam longitudinal, 6061-T6.

Tailgate: 34" high. Includes tailgate chains and offset top hardware.

Hoist: Exclusive J&J model 50725 DA, 15-ton with safety prop.

Lighting: Truck-Lite®, sealed and shock proof system. Body-up light and pto light with premium inside controls.

Other Standard Features: Self-cleaning inside shedder plate • Ladder and steps • Tarp rods • Rear mud flaps and front aluminum mud guards • Back-up alarm

POPULAR OPTIONS

Sides: 30" - 42" height, high tensile, 1/4" thickness.

Cab Protector: 1/2, 3/4, and full.

Floors: 3/8".

Tailgate: 40" - 48". Air operated gates are available. Offset top hardware • Fast latch • 3-way gate fork style with ground control.

Hoist: Model 60825 DA under body hoist, front mount telescopic, twin telescopic, trunnion front mount.

Other: Spreader apron • Full depth rear post with full depth rear skirt • Air operated and hot shift PTO • Body heat • Load covers • Tool box • Coal doors • Pintle hook • Central hydraulics • Special lighting.

*Standard specifications may vary according to customer preferences and requirements. At J&J, we custom build to suit your needs.

		BODY LENGTH			
		9	10	11	12
VOLUME (cu. yds.)	26	4/6	5/7	6/8	7/9
	30	6/7	6/8	7/9	8/9
	36	7/8	8/9	9/10	9/11
	42	8/9	9/10	10/12	11/13

Second capacity indicates cubic yard capacity with 6" board.



This model dump body is a DOT favorite and can be easily outfitted with snow plows and/or spreaders.



Medium duty dump bodies feature 9 - 12 foot aluminum or steel beds.



ISO 9001:2008 Certified

"Our Commitment to Quality"



D.O.T. Registered • A.S.M.E. Certified • National Board Registered



P.O. Box 735
10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.443.2671
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com

Distributed by: