

FTA
EVO Series

Aluminum body, steel frame smooth side trailers are engineered for excavation and construction material hauling.

Our DynaHauler®/FTA EVO Series smooth side aluminum body, steel frame dump trailers are built to handle a variety of demanding applications. Smooth side trailers are fuel efficient and aerodynamic. Whether you're involved in excavating, construction material hauling or any similar application, we can build you a dump trailer that's loaded with standard features and comes with a wide variety of popular options.

Rely on our experience.

There's no substitute for a trailer built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 45 years of experience to build you the transfer trailer you want - we'll build it to your specification and application.

DYNAHAULER® SERIES

J&J EVO Series
The Evolution of Smooth Side!



Optional lift axle HT-250 and tarps are available.

ISO 9001:2000 Certified.
Quality products,
quality workmanship.

J&J Truck Bodies & Trailers is a division
of Somerset Welding & Steel, Inc.

**J&J TRUCK BODIES
& TRAILERS®**
Built for the Long Haul™

Call us today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR ALUMINUM BODY, STEEL FRAME SMOOTH SIDE DUMP TRAILER

ALUMINUM STANDARD SPECIFICATIONS*

Aerodynamically Designed Radius Nose

Side Panels: 54" high smooth side vertical panels.

Floor: 1/4" 5454-H34 solid welded with radius corners. Last 20' of 3/8".

Top & Bottom Rail (30'+): 9" x 4" 6061-T6 top rail. 9" x 4" extruded bottom rail 6061-T6.

Side Posts: Extruded side vertical panels.

Understructure: 4" I-beam crossmembers on 15" centers, 6061-T6. Longitudinals are 6" x 6" x 1/2" angles (6061-T6) running full length, welded to all crossmembers and gusseted to every fourth crossmember.

Tailgate: 54" high, 3/16" 5454-H34, 3-panel.

Lighting: Truck-Lite sealed and shock proof system.

Axles: Dana D-22 25,000 lb., 5" round.

Brakes: 16 1/2" x 7" or 3/4" air operated with ABS.

Frame: 16" deep wide flange beam (31 lb./ft.) high-tensile steel.

Hoist: A variety of front mounted hoists are available, sized to fit body length and payload requirements.

Suspension: HT 300 Hendrickson 60,000 lb.

King Pin: Holland 3/8" A-36 steel.

Landing Gear: Holland Mark V 2-speed, with sand pads. 180,000 lb. static load capacity.

Tires: 11R24.5, 14 ply.

Wheels: 24.5" x 8.25" aluminum polished out, natural in.

Popular Options

Side Panels: A variety of heights are available.

Floor: 3/8" thick 5454-H34.

Understructure: Crossmembers on 12" centers.

Tailgate: Air gates, hydraulic gates, barndoor gates, water tight gates. Sloped or vertical.

Tarping: Tarps, tarp bows and tarp baskets. Manual, electric or hydraulic; slide, arm or roll tarpers.

Optional Features: Tire carrier • Lift axles • Catwalk/Ladders • Toolbox • Spreader apron • Coal door • Air or hydraulic landing gear • Wet-lines • Fifth wheels • On-board scales • Fenders • Vibrators • Centrifuge drums • Aluminum hubs • Square axles • Self-contained power units • Aluminum frame • Shock mounted pad between frame and understructure • Special overhands • Wash-out systems • Sump drains

*Standard specifications may vary according to customer preferences and requirements. Many options are also available. At J&J, we can custom build to suit your needs.



Optional lift axles and tarps are available.



Mud guards, mud flaps, steps and shovel hangers are standard on these trailers.



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

J&J TRUCK BODIES & TRAILERS
Built for the Long Haul™

**P.O. Box 735
10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 1+814.443.2671
Fax: 1+814.443.2621
Toll Free: 1+800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com**