



This trailer will provide you with many years of heavy hauling.

The perfect solution for serious demolition.

The DynaHauler/DT demolition dump trailer is built to work in abusive job-site conditions hauling heavy demolition and construction debris. It comes standard with mud guards, mud flaps, steps, shovel hangers, tarp bars and ABS brakes. Depend on this workhorse for many years of hard work.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

DEMOLITION TRAILER

DYNAHAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

J&J TRUCK BODIES & TRAILERS
Built for the Long Haul®

Call today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR DEMOLITION TRAILER



Convert from conventional gate to a side swing gate in two quick steps with our easy-to-use, optional combination tailgate.



J&J dump trailers set the standard for quality and reliability.

STEEL STANDARD SPECIFICATIONS*

Lengths: 24' to 40'.

Height: 54", 60", 66" or 72".

Side panels: Abrasion resistant 3/16" high hard steel with one (1) row of horizontal side brace posts (centered).

Floor: Abrasion resistant 1/4" high hard steel. Solid welded with radius corners.

Bottom & Top Rail: 1/4" formed high-tensile bottom rail. Top rail is 4"x 4" x 1/4" A-500 structural tubing with inverted dirt shedding angle on top.

Side & Rear Posts: Vertical side posts on 24" centers. Rear posts are 4"x 4" x 1/4" A-500 tubing welded and gusseted to rear crossmember under floor; then reinforced with 12"x 4" formed section.

Understructure: 4" I-beam crossmembers (7.7 lb./ft) on 12" centers. Longitudinals are 6"x 6" x 3/8" angle running full length, welded to all crossmembers and gusseted to every other crossmember.

Tailgate: 1/4" Abrasion resistant high hard steel, 9 panel, barn door type, curbside hinge, driver's side rear positive latching mechanism.

Lighting: Truck-Lite®, sealed and shock proof system.

Axles: Dana, D22, 25,000 lb., 5" round.

Brakes: 16 1/2" x 7" x 3/4 air operated, with ABS 4S2M system.

Frame: 16" deep, wide flange beam (31 lb./ft) high-tensile steel.

Hoist: A variety of front mounted hoists are available, sized to fit body length and payload requirements.

Suspension: 60,000 lb., single point.

King Pin: Holland MarkV, 2-speed, with sand pads 180,000 lb. static load capacity.

Landing Gear: Holland T809 2 7/8" diameter. King pin plate is 3/8" A-36 steel.

Wheels: 24.5 x 8.25 steel hub pilot.

Tires: IIR22.5" or IIR24.5" 14 ply standard.



Lighter weight high hard steel cushioned floor plates absorb impact while maintaining the integrity of the trailer.

Available with: **J&J BODY ARMOR**

*Standard specifications may vary according to customer's preferences and requirements. Many options available.
Call your J&J sales representative today!



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
"Our Commitment to Quality"



J&J TRUCK BODIES & TRAILERS®
Built for the Long Haul®

10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjobodies.com
www.jjobodies.com

Rev: 0916-1