



Optional lift axle HT-250 and tarps are available.

Aluminum body, steel frame smooth side trailers are engineered for excavation and construction material hauling.

Rely on our experience.

Our DynaHauler®/FTA EVO series smooth side aluminum body, steel frame dump trailers are built to handle a variety of demanding applications. Whether you're involved in excavating, construction material hauling, or any similar application, we can build you a dump trailer that's loaded with standard features.

There's no substitute for a trailer built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the trailers you want - we'll build them to your specification and application.



Call today! 800.777.2671
www.jjbodies.com

FRAME TRAILER
ALUMINUM
EVO

DYNAHAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

SPECIFICATIONS & DIMENSIONAL DATA FOR FRAME TRAILER ALUMINUM EVO SERIES



Mud guards, mud flaps, steps, and shovel hangers are standard on these trailers.

ALUMINUM STANDARD SPECIFICATIONS*

Aerodynamically Designed Radius Nose

- Side Panels:** 54" high smooth side vertical panels
- Floor:** 1/4" 5454-H34 solid welded with radius corners. Last 20' of 3/8" Top & Bottom Rail (30'+): 9" x 4" 6061-T6 top rail. 9" x 4" extruded bottom rail 6061-T6
- Side Posts:** Extruded side vertical panels
- Understructure:** 4" I-beam crossmembers on 15" centers, 6061-T6. Longitudinals are 6" x 6" x 1/2" angles (6061-T6) running full length, welded to all crossmembers and gusseted to every fourth crossmember
- Tailgate:** 54" high, 3/16" 5454-H34, 3-panel
- Lighting:** Truck-Lite sealed and shock proof system
- Axles:** Dana D-22 25,000 lb., 5" round
- Brakes:** 16 1/2" x 7" or 3/4" air operated with ABS
- Frame:** 16" deep wide flange beam (31 lb./ft.) high
- Hoist:** A variety of front mounted hoists are available, sized to fit body length and payload requirements
- Suspension:** HT 300 Hendrickson 60,000 lb.
- King Pin:** Holland 3/8" A-36 steel

Landing Gear: Holland Mark V 2-speed, with sand pads. 180,000 lb. static load capacity

Tires: 11R24.5, 14 ply

Wheels: 24.5" x 8.25" aluminum polished out, natural in

POPULAR OPTIONS

- Side Panels:** A variety of heights are available
- Floor:** 3/8" thick 5454-H34
- Understructure:** Crossmembers on 12" centers
- Tailgate:** Air gates, hydraulic gates, barndoor gates, water tight gates. Sloped or vertical
- Tarping:** Tarps, tarp bows, and tarp baskets. Manual, electric or hydraulic; slide, arm, or roll tarpers
- Optional Features:** Tire carrier - Lift axles - Catwalk/Ladders - Toolbox - Spreader apron - Coal door - Air or hydraulic landing gear - Wetlines - Fifth wheels - On-board scales - Fenders - Vibrators - Centrifuge drums - Aluminum hubs - Square axles - Self-contained power units - Aluminum frame - Shock mounted pad between frame and understructure - Special overhands - Wash-out systems - Sump drains

*Standard specifications may vary according to customer's preferences and requirements.
Many options available. **Call your J&J sales representative today!**



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2016 Certified
"Our Commitment to Quality"



10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com