



Spec an optional steel floor to make this dump body an extreme-duty workhorse that's capable of handling the toughest loads day in and day out.

The DynaHauler/HCX is built to work heavy construction.

The HCX dump body is a high performance aluminum dump body designed for heavy-duty hauling applications. The reinforced side brace adds the extra strength required to withstand heavy loads and the aluminum material maximizes payload. Owner/operators invest in the HCX dump body because it delivers years of hard work and reliable service.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trucks you want - we'll build them to your specification and application.

HCX dump bodies are available in aluminum, steel, or stainless.



Call today! 800.777.2671
www.jjbodies.com

HCX

HEAVY
CONSTRUCTION
ALUMINUM

DYNAHAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

SPECIFICATIONS & DIMENSIONAL DATA FOR DYNHAULER/HCX HEAVY CONSTRUCTION DUMP BODIES



J&J Material Hauler dump bodies are designed to maximize payload.



Additional side brace, light packages, and polished aluminum are popular options.

ALUMINUM STANDARD SPECIFICATIONS*

Lengths: 13' to 20'.

Side Panels & Bulkhead: 1/4" 5052-H32 with vertical and horizontal side braces, 54" high, with 4" x 4" 6061-T6 extruded top rail and 7" side boards with center gussets

Floor: 3/8", 5083-H116

Understructure: 6061-T6, 6" I-beam longitudinals, 4" I-beam cross members on 12" centers, 6061-T6, 2" extruded rubber mounting strip.

Cab Protector: 3/16," full length/full width, load bearing.

Tailgate: 60" high, 6 panel, 3/8" with offset top hardware.

Hydraulic System: Front mount telescopic cylinder, PTO & pump, 3-line safety system, variety of controls and instrumentation to suit requirements.

Lighting: Meets FMVSS 108 guidelines, LED standard, variety of configurations and warning modules available.

Popular Options: Body Armor™ steel floor • Polished aluminum • Spreader apron • Air operated pump and premium Chelsea PTO • Hot shift PTO • Body heat • Tarp



In addition to the optional combination tailgate shown here, air operated high lift gates are also available.

For a complete list of options, call J&J today!

Available with **BODY ARMOR™** steel floor.

		BODY LENGTH								
VOLUME (cu. yds)	SIDE	13	14	15	16	17	18	19	20	
	42	12/14	13/15	14/16	15/18	16/19	17/20	18/21	19/22	
	48	14/16	15/17	16/19	17/20	18/21	19/22	20/24	21/25	
	54	15/18	17/19	18/21	19/22	20/23	22/25	23/26	24/28	
	60	17/20	19/21	20/23	21/24	23/26	24/27	25/29	27/30	
	66	19/21	20/23	22/25	24/26	25/28	27/30	28/31	30/33	

*Standard specifications may vary according to customer's preferences and requirements. Many options available.

Call your J&J sales representative today!



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
"Our Commitment to Quality"



**10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjobodies.com
www.jjobodies.com**