

Increase productivity and maximize profit.

The efficient and purpose-built design of our dump body and chassis combination allows for speed and stability while providing increased productivity per cycle and maximum profit per ton hauled. The dump body is constructed of steel and is designed to handle the most extreme materials.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trucks you want - we'll build them to your specification and application.

OFF ROAD DYNNHAULER

ISO 9001:2015 Certified. Quality products, quality workmanship.

J&J Třučk Bodies & Třailers iš a division of Somerset Welding & Stěel, Inc.



Call today! 800.777.2671 www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR OFF ROAD DYNAHAULER

WEIGHT DISTRIBUTION AND PAYLOAD - DUMP BODY

	LBS	KG
Front Axle (tare):	18,400	8,346
Tandem Rear Axle (tare):	32,600	14,787
Total Unladen Vehicle Weight:	51,000	23,133
Available Payload Capacity:	80,000	36,287
Total Laden Vehicle Weight:	131,000	59,420

LOAD CAPACITY	Cubic Yards	Cubic Meters
Struck Capacity:	26.2	20
Heaped Capacity:	32.7	25

DIMENSIONS	Inches	Millimeters
Length:	217	5512
Width:	129.5	3289
Height:	57	1448

MATERIAL	Inches	Millimeters
Sides:	3/8" steel	10mm steel
Floor:	1/2" steel	13mm steel
Tailgate:	3/8" steel	10mm steel
Cab Guard:	1/4" Hi-Ten	6mm Hi-Ten

^{*}Standard specifications may vary according to customer's preferences and requirements. Many options available. Call your J&J sales representative today!

OPTIONAL COMPONENTS

COLD WEATHER PACKAGE

Block Heater and Ether Start Minus 60 Degree Farenheit Engine Coolant

Fuel Water Separator with Coolant Heat

Heated Dump Body

LIGHT PACKAGES (Back Up & STT in Frame Standard)

Marker and Clearance Lights Strobes/Hazards Lights Rotating Beacons Mounted to Cab Roof Work Lights

ADDITIONAL OPTIONS

Auto Assist Tailgate 1/2" HARDOX Liner Strips 5/8" HARDOX Liner Strips Material Ejectors Rock Guard Rear Tube Bumper **Automatic Greasing System** Fire Extinguisher Deluxe First Aid Kit

Available with:



For a complete list of options, call J&J today!



The low profile sides are designed for easy and efficient loading with a scowled end to secure large boulders and reduce hydraulic cylinder stress upon boulder impact.



The auto lift tailgate maximizes material loading while the full cab guard protects the operators in the cab from falling debris.

HOIST AND HYDRAULICS

Front Mounted Single Acting Four-Stage Hydraulic Cylinder Hydraulic System Flow @ 1500 RPM: 41 GPM / 144 LPM

Hydraulic System Pressure: 2500 PSI / 172 BAR

Body Angle: 55 Degrees

Body Raise Time @ 1500 RPM: 18 Seconds

Body Lower Time: 16 Seconds

A B	
Æ T	EP.

D.O.T. Registered · A.S.M.E. Certified · National Board Registered

Distributed by:

ISO 9001:2015 Certified "Our Commitment to Quality"





10558 Somerset Pike Somerset, PA 15501 USA Phone: 814.444.3400 Fax: 814.443.2621

Toll Free: 800.777.2671 (USA only)

Email: sales@jjbodies.com www.jjbodies.com

Rev: 1216-2