



*Trailer shown  
with open-top  
and standard side  
swing tailgate.*

## **Ideal for disaster clean-up & rollover prevention.**

J&J Steel Push Out Trailers eject horizontally and are uniquely designed to safely haul and discharge refuse and other like materials. Because of their size and stability, our trailers allow operators to haul maximum payload with less chance of rollover.

## **Rely on our experience.**

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 60+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

**J&J**  
**STEEL PUSH  
OUT OPEN  
TOP TRAILERS**

**DYNAMAULER**

**ISO 9001:2015 Certified.**  
**Quality products,  
quality workmanship.**

*J&J Truck Bodies & Trailers  
is a division of  
Somerset Welding & Steel, Inc.*

**J&J TRUCK BODIES  
& TRAILERS®**  
Built for the Long Haul™

**Call today! 800.777.2671**  
**[www.jjbodies.com](http://www.jjbodies.com)**

# SPECIFICATIONS & DIMENSIONAL DATA FOR STEEL PUSH OUT OPEN TOP TRAILERS



Tractor hook-ups and hydraulic controls located in one area for ease of operation. Trailer shown with optional trailer mounted hydraulic tank.



Fully self-contained trailer shown with auxiliary engine, retractable roof and hydraulic lift and lock compactor tailgate.

## STEEL STANDARD SPECIFICATIONS\*

- Lengths:** 45'
- Height:** 72"
- Side Panels:** Front 12 ga., rear 1/3 10 ga. high-tensile.
- Floor:** 3/16" high-tensile
- Side Posts:** 12 ga. high-tensile, 24" spacing.
- Crossmembers:** 12 ga. high-tensile.
- Ejector:** 10 ga. high-tensile face plate, 3/16" & 1/4" high-tensile, 4" boxed brace members
- Ejector Hydraulic System:** To suit tractor.
- Rear Door:** 12 ga. high-tensile side swing tailgate.
- Suspension:** Tandem REYCO-52,000# capacity.
- Hub & Drum Assembly:** 10 hole hub piloted.
- Rims:** 8.25 x 22.5.
- Tires:** 11R22.5, 14 ply.
- Axles:** 25,000# capacity.
- Lighting:** Truck-Lite® sealed harness.
- Landing Gear:** Holland MK-V 200,000# static load, 62,500@ lift.
- King Pin:** Holland T-880.
- Cylinders:** Custom 95-439 5 stage.



Ejector ram cylinder is sized to completely unload trailer and the replaceable UHMW wipers on top and sides of ejector ram provide superior clean-out.

Available with:



\*Standard specifications may vary according to customer's preferences and requirements. Many options available.

**Call your J&J sales representative today!**



D.G.E. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:



**10558 Somerset Pike**  
**Somerset, PA 15501 USA**  
**Phone: 814.444.3400**  
**Fax: 814.443.2621**  
**Toll Free: 800.777.2671 (USA only)**  
**Email: sales@jjbodies.com**  
**www.jjbodies.com**

Rev: 0120-1